

# 10,4" LCD-TFT Monitor

## DMXX 3209/3210/3211/3212



### Key Features

Very High Brightness  
Wide Viewing Angle  
High Contrast Ratio  
LVDS  
Long Lamp Life  
Short Response Time  
Thin and Light

<b>LCD Display</b>	10,4" TFT Active Matrix Panel
<b>TouchScreen</b>	optional
<b>Brightness</b>	1.500 cd/m <sup>2</sup>
<b>Pixel Pitch</b>	0.264 (H) x 0.264(V) mm
<b>Max. Resolution</b>	800 x 600 (SXGA)
<b>Contrast Ratio</b>	500:1
<b>Display Area</b>	211.2 x 158.4mm
<b>Response Time</b>	35ms (Typ.)
<b>Display Colors</b>	262,144 colors
<b>Viewing Angle</b>	+60° ~ -60° (H), +40° ~ -60° (V)
<b>Video</b>	RGB Analog 0.7V Peak to Peak
<b>Sync</b>	LVDS
<b>Signal Connector</b>	15 Pin D-sub, S-Video, AV
<b>F/R Control Button</b>	Power Switch, Menu, Select (+,-)
<b>OSD Menu</b>	Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
<b>Power Consumption</b>	30W
<b>Anti-glare Glass</b>	Power Switch, Menu, Select (+,-), Auto
<b>Dimensions</b>	340 x 228 x 54.2mm (WxHxD)
<b>Weight</b>	3.15kg
<b>Connectors</b>	VGA/AV/S-Video

### Ordering Information:

<b>DMXX3209</b>	10.4" TFT-LCD Monitor 800 x 600 VGA/AV/S-Video High Brightness Einbaumonitor 1.500cd/m <sup>2</sup> , ohne Touch
<b>DMXX3210</b>	10.4" TFT-LCD Monitor 800 x 600 VGA/AV/S-Video High Brightness Einbaumonitor 1.500cd/m <sup>2</sup> , mit Touch LiYi resistiv
<b>DMXX3211</b>	10.4" TFT-LCD Monitor 800 x 600 VGA/AV/S-Video High Brightness Einbaumonitor 1.500cd/m <sup>2</sup> , mit Touch 3M resistiv
<b>DMXX3212</b>	10.4" TFT-LCD Monitor 800 x 600 VGA/AV/S-Video High Brightness Einbaumonitor 1.500cd/m <sup>2</sup> , mit Touch 3M kapazitiv