

8.9" Digital Signage Panel PC

PKDS3000



The Digital Signage Panel PC series is cost effective yet high performance all-in-one digital signage display designed to address a broad spectrum of digital signage applications. The 8.9" Digital Signage Panel PC is an Intel® Atom™ N270 based digital signage player with built-in high quality 8.9" 16:9 LCD display pre-loaded with user-friendly digital signage software, targeting for entry-level digital signage applications. The 8.9" Digital Signage Panel PC is a self-contained digital signage display and player device enclosed in a compact chassis with low power consumption. The 8.9" Digital Signage Panel PC is capable to layout display into multiple rectangle zones and play rich multi-media contents on each zone in accordance with user defined schedule table. This makes the 8.9" Digital Signage Panel PC work perfect for increasing digital signage applications within retail outlets, department store, entertainment venues, restaurants, hotels, bus/train station, schools/universities and hospitals for dynamic message delivering, advertising, or brand promotion.



Presentation Design Tool

The presentation design tool is one of the most valuable parts of the Digital Signage software. It helps digital signage content creator on intuitive operations to ease the output of presentation to the player. The tool provides quick screen layout design function. The screen layout can be saved as template for reuse. The tool provides an easy drag and drop method to organize contents in playlist and associate playlist to each zones in the screen layout. The tool provides handy preview function for individual content files and final presentation. The presentation design tool also integrates easy upload function to publish presentation design to removable media, central management server, or player.

Applications

- Retail outlets
- Department stores
- Entertainment venues
- Restaurants
- Hotels
- Bus/train station
- Schools/universities
- Hospitals

User's Benefits

- Seamless hardware and software integration for operation reliability
- Flexible display configuration
- Presentation design is simple and intuitive
- Presentation publish and scheduling is easy
- Presentation content support is rich and versatile
- All-In-one design, Easy installation, Plug and play

8.9" Digital Signage Panel PC

PKDS3000



Software Specification

Content Source

- Local disk or network server

Video File Format

- MPEG1/2, AVI, VOB, MOV, WMV, VC-1, H.264

Flash File Format

- SWF

Picture File Format

- JPG, TIFF, ICP, PNG, GIF, BMP, WMF

Sound Format

- WAV, SND, MP3, M4A

Web/Data

- Web URL
- Text files
- RSS news feed

Screen Support

- Single display, or two clone displays
- Portrait or Landscape orientation
- Presentation can be segmented to different screen layouts
- Up to 9 display zones in each screen layout

Playing Effect

- Scrolling text and emergency message
- Image transition effect
- Multiple languages

Content Throughput

- Up to 1x HD video zone or 1x shockwave flash zone

Management Function

- Web-based management with password access control
- Multilingual management interface
- Presentation management
- Presentation scheduling
- System event log
- Presentation playing log
- Presentation play/Pause/Stop control function
- System reboot, Shutdown, Firmware upgrade

Presentation Design

- Presentation layout and playlist editing function
- Presentation and content file preview function
- Presentation publish function

OS

- Windows XP Embedded

Hardware Specification

CPU

- Intel® Atom™ N270 1.6GHz, 512KB L2 Cache

Main Memory

- 1GB DDR2 SDRAM

Storage Device

- 160GB SATA HDD

Display

- TFT LCD panel 8.9" 16:9
- 1.024x600 WSVGA resolution
- Optional TouchScreen

I/O Interface

- 1x DB15 VGA
- 1x Audio line-out
- 2x RJ45 with LEDs for 10/100/1000Mbps Ethernet
- 2x USB 2.0 port
- 2x DB9 for RS-232

Power Supply

- 1x External AC/DC adapter
- Input: 100-240VAC
- Output: +12VDC

Dimensions

- 225 x 53.9 x 139 mm (W x D x H)

Environment

- Operating Temperature 0°C to +40°C (ambient with air flow)
- Storage Temperature -20°C to +75°C
- Operating Humidity: 10 to 90% (non-condensing)

Certifications

- CE approval
- FCC class A

Ordering Information

PKDS3000 8.9" Digital Signage Panel PC
Intel Atom N270 1.6GHz, 1GB memory