

Embedded Systems - Cost-effective Solution

Selection Guide



Page 205



Page 206



Page 207



Page 208

Features/Models	eBOX510-820-FL	eBOX530-820-FL	eBOX620-831-FL	eBOX621-831-FL
CPU Level	Intel® Atom™ Z510 1.1 GHz/ Z530 1.6 GHz	Intel® Atom™ Z510 1.1 GHz/ Z530 1.6 GHz	Intel® Atom™ N270 1.6 GHz	Intel® Atom™ N270 1.6 GHz
System Memory	1 x 200-pin DDR2 SODIMM max. up to 2 GB	1 x 200-pin DDR2 SODIMM max. up to 2 GB	1 x 200-pin DDR2 SODIMM max. up to 2 GB	1 x 200-pin DDR2 SODIMM max. up to 2 GB
Chipset	Intel® US15W core logic	Intel® US15W core logic	Intel® 945GSE+ICH7M	Intel® 945GSE+ICH7M
Serial	1 x RS-232 (COM 1)	2 x RS-232 (COM 1/2)	3 x RS-232 (COM 1/2/3)	3 x RS-232 (COM 1/2/3)
Display	1 x VGA	1 x VGA	1 x VGA	1 x VGA
Audio	1 x Audio (Line-out)	1 x Audio (Line-in/Line-out)	1 x Audio (Line-in/Line-out)	1 x Audio (Line-in/Line-out)
LPT	N/A	N/A	N/A	N/A
PS/2	1 x PS/2 keyboard/mouse	1 x PS/2 keyboard/mouse	1 x PS/2 keyboard/mouse	1 x PS/2 keyboard/mouse
Ethernet	1 x 10/100/1000Mbps Ethernet	1 x 10/100/1000Mbps Ethernet	2 x 10/100/1000Mbps Ethernet	2 x 10/100/1000Mbps Ethernet
USB	4 x USB 2.0	4 x USB 2.0	4 x USB 2.0	4 x USB 2.0
Expansion Interface	N/A	N/A	N/A	N/A
Storage	1 x CompactFlash™	1 x 2.5" HDD 1 x CompactFlash™	1 x 2.5" HDD 1 x CompactFlash™	1 x 2.5" HDD 1 x CompactFlash™
Watchdog Timer	255 levels, 1 - 255 sec.	255 levels, 0 - 255 sec.	255 levels, 1 - 255 sec.	255 levels, 1 - 255 sec.
Power Supply	25W 100 - 240V _{AC} adapter	25W 100 - 240V _{AC} adapter	60W 115 - 230V _{AC} adapter	42.5W 9 - 34V _{DC} adapter
Operating Temperature	0°C - +50°C (32°F - 122°F) (with W.T. CF)	0°C - +45°C (32°F - 113°F) (with W.T. HDD)	-10°C - +50°C (14°F - 122°F) (with W.T. HDD)	-10°C - +50°C (14°F - 122°F) (with W.T. HDD)
Extended Temperature (Sorting)	N/A	N/A	N/A	N/A
Wall Mount	Yes	Yes	Yes	Yes
DIN-rail	Yes	Yes	Yes	Yes
Dimensions (W x D x H)	132 x 95.4 x 37.5 mm (5.19" x 3.75" x 1.47")	132 x 95.4 x 47.5 mm (5.19" x 3.75" x 1.85")	200 x 120 x 56 mm (7.87" x 4.72" x 2.2")	200 x 120 x 56 mm (7.87" x 4.72" x 2.2")
Weight (net/gross)	0.48 kg (1.06 lb)/0.5 kg (1.1 lb)	0.5 kg (1.1 lb)/0.6 kg (1.32 lb)	1.8 kg (3.97 lb)/2.6 kg (5.73 lb)	1.8 kg (3.97 lb)/2.6 kg (5.73 lb)
Certification	CE	CE	CE	CE
EOS Support	XPE, CE, Linux	XPE, CE, Linux	XPE, CE, Linux	XPE, CE, Linux

Embedded Systems - Cost-effective Solution

Selection Guide



Page 209



Page 210



Page 211

Features\Models	eBOX620-823-FL	eBOX630-821-FL	eBOX630-830-FL
CPU Level	Intel® Atom™ Z510PT (1.1 GHz)/ Z520PT (1.33 GHz)	ULV Intel® Celeron® M 600 MHz/512 KB Intel® Pentium® M/ Celeron® M up to 2.0 GHz	ULV Intel® Celeron® M 1.06 GHz/ Intel® Core™2 Duo/Core™ Duo/ Core™ solo/Celeron® M up to 2.33 GHz
System Memory	1 x 200-pin DDR2 SODIMM max. up to 2 GB	1 x 200-pin DDR2 SODIMM max. up to 2 GB	1 x 200-pin DDR2 SODIMM max. up to 2 GB
Chipset	Intel® US15WPT core logic	Intel® 915GME/910GML+ICH6M	Intel® 945GME+ICH7M
Serial	2 x RS-232 (COM 1/2)	3 x RS-232 (COM 2/3/4) 1 x RS-232/422/485 (COM 1)	3 x RS-232 (COM 2/3/4) 1 x RS-232/422/485 (COM 1)
Display	1 x VGA	1 x VGA 1 x DVI-D (optional)	1 x DVI-I 1 x DVI-D (optional)
Audio	1 x Audio (Line-in/Line-out)	1 x Audio (Mic-in/Line-out)	1 x Audio (Mic-in/Line-out)
LPT	N/A	N/A	N/A
PS/2	1 x PS/2 keyboard/mouse	1 x PS/2 keyboard/mouse	1 x PS/2 keyboard/mouse
Ethernet	1 x 10/100/1000Mbps Ethernet	2 x 10/100/1000Mbps Ethernet	2 x 10/100/1000Mbps Ethernet
USB	4 x USB 2.0	4 x USB 2.0	4 x USB 2.0
Expansion Interface	1 x PCI Express Mini Card (USB only)	N/A	N/A
Storage	1 x 2.5" HDD 1 x CompactFlash™	1 x 2.5" HDD 1 x CompactFlash™	1 x 2.5" HDD 1 x CompactFlash™
Watchdog Timer	255 levels, 1 - 255 sec.	255 levels, 0 - 255 sec.	255 levels, 0 - 255 sec.
Power Supply	36W 12 - 24V _{DC} adapter	60W 115 - 230V _{AC} adapter	60W 115 - 230V _{AC} adapter
Operating Temperature	-20°C - +70°C (-4°F - +158°F) (with W.T. HDD)	0°C - +50°C (32°F - 122°F) (with W.T. HDD)	0°C - +50°C (32°F - 122°F) (with W.T. HDD)
Wall Mount	Yes	Yes	Yes
DIN-rail	Yes	N/A	N/A
Dimensions (W x D x H)	200 x 120 x 56 mm (7.87" x 4.72" x 2.2")	280 x 150 x 67 mm (11.02" x 5.91" x 2.64")	280 x 150 x 67 mm (11.02" x 5.91" x 2.64")
Weight (net/gross)	1.8 kg (3.97 lb)/2.6 kg (5.73 lb)	2.5 kg (5.51 lb)/4.5 kg (9.92 lb)	2.5 kg (5.51 lb)/4.5 kg (9.92 lb)
Certification	CE	CE	CE
EOS Support	XPE, CE, Linux	XPE, WinCE, Linux	XPE, WinCE, Linux

Embedded Systems - Cost-effective Solution

Selection Guide



Page 212



Page 213



Page 214

Features\Models	eBOX640-822-FL	eBOX738-FL	eBOX745-FL500
CPU Level	Intel® Celeron® M 1.0 GHz Intel® Pentium® M/Celeron® M up to 2.0 GHz	Intel® Celeron® M 600 MHz Intel® Celeron® M 1.0 GHz Intel® Celeron® M 1.5 GHz Intel® Pentium® M 1.1 GHz Intel® Pentium® M 1.4 GHz	AMD® Geode LX800 500 MHz
System Memory	2 x 240-pin DDR2 DIMM max. up to 2 GB	1 x 184-pin DDR DIMM max. up to 1 GB	1 x 200-pin DDR SODIMM max. up to 1 GB
Chipset	Intel® 910GML+ICH6M	Intel® 855GME/852GM+6300ESB	AMD LX800+CS5536
Serial	6 x RS-232 (COM 1-6)	3 x RS-232 (COM 1/2/3) 1 x RS-232/422/485 (COM 2)	3 x RS-232 (COM 2/3/4) 1 x RS-232/422/485 (COM 1)
Display	1 x VGA	1 x VGA	1 x VGA
Audio	1 x Audio (Mic-in/Line-out)	N/A	N/A
LPT	N/A	1 x LPT	1 x LPT
PS/2	1 x PS/2 keyboard/mouse	1 x PS/2 keyboard/mouse	1 x PS/2 keyboard/mouse
Ethernet	2 x 10/100/1000Mbps Ethernet	1 x 10/100Mbps Ethernet 1 x 10/100/1000Mbps Ethernet (optional)	2 x 10/100Mbps Ethernet
USB	6 x USB 2.0	2 x USB 2.0	3 x USB 2.0
Expansion Interface	N/A	1 x PCI104	N/A
Storage	1 x 2.5" HDD	1 x 2.5" HDD 1 x CompactFlash™	1 x 2.5" HDD 1 x CompactFlash™
Watchdog Timer	255 levels, 0 - 255 sec.	1024 levels, 0 - 600 sec.	255 levels, 0 - 255 sec.
Power Supply	107W ATX 16 - 28Vdc	110W ATX 110 - 264VAc 100W ATX 12Vdc/24Vdc	72W AT 85 - 270VAc 72W AT 18 - 36Vdc
Operating Temperature	-10°C - +50°C (14°F - 122°F) (with W.T. HDD)	-20°C - +50°C (-4°F - +122°F) (with W.T. HDD)	-20°C - +50°C (-4°F - +122°F) (with W.T. HDD)
Wall Mount	Yes	Yes	Yes
DIN-rail	Yes	N/A	Yes
Dimensions (W x D x H)	182 x 230 x 89 mm (7.17" x 9.06" x 3.5")	225 x 275 x 90 mm (8.86" x 10.83" x 3.54")	225 x 225 x 51 mm (8.86" x 8.86" x 2.01")
Weight (net/gross)	3.1 kg (6.83 lb)/3.8 kg (8.38 lb)	4.5 kg (9.92 lb)/5 kg (11.02 lb)	2.15 kg (4.74 lb)/2.9 kg (6.39 lb)
Certification	CE	CE	CE
EOS Support	XPE, WinCE, Linux	XPE, WinCE, Linux	XPE, WinCE, Linux

Embedded Systems - Cost-effective Solution

Selection Guide



Page 215



Page 216



Page 217

Features/Models	eBOX746A-FL	eBOX748-FL	eBOX748-820-FL
CPU Level	VIA Eden 1 GHz VIA C7 1.5 GHz	Intel® Celeron® M 600 MHz Intel® Celeron® M 1.0 GHz Intel® Pentium® M 1.1 GHz Intel® Pentium® M 1.4 GHz	Intel® Celeron® M 1.0 GHz Intel® Pentium® M 1.4 GHz
System Memory	1 x 200-pin DDR2 SODIMM max. up to 1 GB	1 x 200-pin DDR SODIMM max. up to 1 GB	1 x 200-pin DDR2 SODIMM max. up to 1 GB
Chipset	VIA CX700M	Intel® 852GM+ICH4	Intel® 915GM/910GMLE+ICH6M
Serial	3 x RS-232 (COM 2/3/4) 1 x RS-232/422/485 (COM 1)	1 x RS-232 (COM 2) 1 x RS-232/422/485 (COM 1) (Optional COM 3-8)	1 x RS-232 (COM 2) 1 x RS-232/422/485 (COM 1)(Optional COM 3-8)
Display	1 x VGA	1 x VGA 1 x DVI-D (optional)	1 x VGA 1 x DVI-D or VGA (optional)
Audio	N/A	1 x Audio (Mic-in/Line-in/Line-out)	1 x Audio (Mic-in/Line-in/Line-out)
LPT	1 x LPT	1 x LPT	1 x LPT
PS/2	1 x PS/2 keyboard/mouse	1 x PS/2 keyboard/mouse	1 x PS/2 keyboard/mouse
Ethernet	1 x 10/100Mbps Ethernet 1 x 10/100/1000Mbps Ethernet (optional)	1 x 10/100Mbps Ethernet 1 x 10/100/1000Mbps Ethernet (optional)	1 x 10/100Mbps Ethernet 1 x 10/100/1000Mbps Ethernet (optional)
USB	3 x USB 2.0	4 x USB 2.0	4 x USB 2.0
Expansion Interface	N/A	N/A	N/A
Storage	1 x 2.5" HDD 1 x CompactFlash™	1 x 2.5" HDD 1 x CompactFlash™	1 x 2.5" HDD 1 x CompactFlash™
Watchdog Timer	255 levels, 0-255 sec.	255 levels, 0-255 sec.	255 levels, 0-255 sec.
Power Supply	70W AT 85 - 270V _{AC} 72W AT 18 - 36V _{DC}	80W ATX 100 -2 40V _{AC} 72W AT 10 - 34V _{DC}	80W ATX 90 - 264V _{AC} 70W ATX 9 - 32V _{DC}
Operating Temperature	-10°C ~ +50°C (14°F ~ 122°F) (with W.T. HDD)	-10°C ~ +50°C (14°F ~ 122°F) (with W.T. HDD)	-10°C ~ +50°C (14°F ~ 122°F) (with W.T. HDD)
Wall Mount	Yes	Yes	Yes
DIN-rail	Yes	N/A	N/A
Dimensions (W x D x H)	225 x 225 x 63 mm (8.86" x 8.86" x 2.48")	205 x 50 x 56 mm (8.07" x 9.84" x 2.2")	205 x 50 x 56 mm (8.07" x 9.84" x 2.2")
Weight (net/gross)	2.65 kg (5.84 lb)/4.2 kg (9.26 lb)	2.84 kg (6.26 lb)/4.1 kg (9.04 lb)	2.84 kg (6.26 lb)/4.1 kg (9.04 lb)
Certification	CE	CE	CE
EOS Support	XPE, WinCE, Linux	XPE, WinCE, Linux	XPE, WinCE, Linux

Embedded Systems - Expansible Solution

Selection Guide



Page 218



Page 219



Page 220

Features\Models	eBOX638-FL	eBOX639-836-FL	eBOX639-822-FL
CPU Level	Intel® Celeron® M 600 MHz Intel® Celeron® M 1.0 GHz Intel® Pentium® M 1.1 GHz Intel® Pentium® M 1.4 GHz	Intel® Atom™ N270 1.6 GHz	Intel® Celeron® M 1.0 GHz Intel® Pentium® M/Celeron® M up to 2.0 GHz
System Memory	1 x 184-pin DDR DIMM max. up to 1 GB	1 x 240-pin DDR2 SODIMM max. up to 2 GB	2 x 240-pin DDR2 DIMM max. up to 2 GB
Chipset	Intel® 855GME/852GM+6300ESB	Intel® 945GSE+ICH7M	Intel® 910GML+ICH6M
Serial	3 x RS-232 (COM 1/3/4) 1 x RS-232/422/485 (COM 2)	5 x RS-232 (COM 2-6) 1 x RS-232/422/485 (COM 1)	6 x RS-232 (COM 1-6)
Display	1 x VGA	1 x VGA	1 x VGA
Audio	1 x Audio (Mic-in/Line-in/Line-out)	1 x Audio (Line-in/Line-out)	1 x Audio (Mic-in/Line-out)
LPT	1 x LPT	N/A	1 x LPT
PS/2	1 x PS/2 keyboard/mouse	1 x PS/2 keyboard/mouse	1 x PS/2 keyboard/mouse
Ethernet	2 x 10/100Mbps Ethernet	2 x 10/100/1000Mbps Ethernet	2 x 10/100/1000Mbps Ethernet
USB	4 x USB 2.0	6 x USB 2.0	6 x USB 2.0
Expansion Interface	2 x PCI-X (supports PCI) 1 x PCI104	2 x PCI 1 x CompactFlash™	2 x PCI
Storage	1 x 2.5" HDD 1 x CompactFlash™	1 x 2.5" HDD 1 x CompactFlash™	1 x 2.5" HDD
Watchdog Timer	1024 levels, 0 - 600 sec.	255 levels, 1 - 255 sec.	255 levels, 0 - 255 sec.
Power Supply	100W ATX 12Vdc/24Vdc	107W ATX 16 - 28Vdc	107W ATX 16 - 28Vdc
Operating Temperature	-10°C - +50°C (14°F - 122°F) (with W.T. HDD)	-10°C - +55°C (14°F - 131°F) (with W.T. HDD)	-10°C - +50°C (14°F - 122°F) (with W.T. HDD)
Wall Mount	Yes	Yes	Yes
DIN-rail	N/A	N/A	N/A
Dimensions (W x D x H)	180 x 230 x 126.2 mm (7.09" x 9.06" x 4.98")	182 x 230 x 130.8 mm (7.17" x 9.06" x 5.15")	182 x 230 x 130.8 mm (7.17" x 9.06" x 5.15")
Weight (net/gross)	3.67 kg (8.09 lb)/4.8 kg (10.58 lb)	4.1 kg (9.04 lb)/4.8 kg (10.58 lb)	4.1 kg (9.04 lb)/4.8 kg (10.58 lb)
Certification	CE	CE	CE
EOS Support	XPE, WinCE, Linux	XPE, CE, Linux	XPE, WinCE, Linux

Embedded Systems - Expansible Solution

Selection Guide



Page 221



Page 222



Page 223

Features/Models	eBOX639-840-FL	eBOX830-822-FL	eBOX830-831
CPU Level	Socket P Intel® Core™2 Duo/ Celeron® M up to 2.2 GHz	Intel® Pentium® M/ Celeron® M up to 2.0 GHz	Intel® Core™2 Duo/ Core™ Duo/Celeron® M up to 2.33 GHz
System Memory	2 x 240-pin DDR2 DIMM max. up to 4 GB	2 x 240-pin DDR2 DIMM max. up to 2 GB	2 x 240-pin DDR2 DIMM max. up to 4 GB
Chipset	Intel® GME965+ICH8M	Intel® 910GML+ICH6M	Intel® 945GME+ICH7M/-DH
Serial	3 x RS-232 (COM 2/3/4) 1 x RS-232/422/485 (COM 1)	6 x RS-232 (COM 1-6)	3 x RS-232 (COM 2/3/4) 1 x RS-232/422/485 (COM 1)
Display	1 x VGA	1 x VGA	1 x VGA
Audio	1 x Audio (Mic-in/Line-out)	1 x Audio (Mic-in/Line-out)	1 x Audio (Mic-in/Line-out)
LPT	N/A	N/A	N/A
PS/2	1 x PS/2 keyboard/mouse	2 x PS/2 keyboard/mouse	2 x PS/2 keyboard/mouse
Ethernet	2 x 10/100/1000Mbps Ethernet	2 x 10/100/1000Mbps Ethernet	2 x 10/100/1000Mbps Ethernet
USB	6 x USB 2.0	6 x USB 2.0	6 x USB 2.0
Expansion Interface	2 x PCI or 1 x PCIe x16 & 1 x PCI	1 x PCI	1 x PCI
Storage	1 x 2.5" HDD	1 x 2.5" HDD	1 x 2.5" HDD
Watchdog Timer	255 levels, 0 - 255 sec.	255 levels, 0 - 255 sec.	255 levels, 0 - 255 sec.
Power Supply	150W ATX 10 - 30Vbc	120W ATX 90 - 264VAc	250W ATX 90 - 264VAc
Operating Temperature	-10°C - +40°C (14°F - 104°F) (with W.T. HDD)	0°C - +45°C (32°F - 113°F) (with W.T. HDD)	0°C - +45°C (32°F - 113°F) (with W.T. HDD)
Wall Mount	Yes	Yes	Yes
DIN-rail	N/A	N/A	N/A
Dimensions (W x D x H)	182 x 230 x 140 mm (7.17" x 9.06" x 5.51")	300 x 210 x 104.5 mm (11.81" x 8.27" x 4.11")	300 x 210 x 104.5 mm (11.81" x 8.27" x 4.11")
Weight (net/gross)	4.5 kg (9.92 lb)/5.0 kg (11.02 lb)	6.3 kg (13.89 lb)/8 kg (17.64 lb)	6.3 kg (13.89 lb)/8 kg (17.64 lb)
Certification	CE	CE	CE
EOS Support	XPE, WinCE, Linux	N/A	XPE, WinCE, Linux

Embedded Systems - Expansible Solution

Selection Guide



Page 224



Page 225



Page 226

Features/Models	eBOX830-831-FL	eBOX832-831	eBOX832-840
CPU Level	Intel® Celeron® M/ LV Intel® Core™2 Duo 1.5 GHz (L7400)	Intel® Core™2 Duo/ Core™ Duo/Celeron® M up to 2.33 GHz	Intel® Core™2 Duo/ Celeron® M up to 2.2 GHz
System Memory	2 x 240-pin DDR2 DIMM max. up to 4 GB	2 x 240-pin DDR2 DIMM max. up to 4 GB	2 x 240-pin DDR2 DIMM max. up to 4 GB
Chipset	Intel® 945GME+ICH7M/-DH	Intel® 945GME+ICH7M/-DH	Intel® GME965+ICH8M
Serial	3 x RS-232 (COM 2/3/4) 1 x RS-232/422/485 (COM 1)	3 x RS-232 (COM 2/3/4) 1 x RS-232/422/485 (COM 1)	3 x RS-232 (COM 2/3/4) 1 x RS-232/422/485 (COM 1)
Display	1 x VGA	1 x VGA	1 x VGA
Audio	1 x Audio (Mic-in/Line-out)	1 x Audio (Mic-in/Line-out)	1 x Audio (Mic-in/Line-out)
LPT	N/A	N/A	N/A
PS/2	2 x PS/2 keyboard/mouse	2 x PS/2 keyboard/mouse	2 x PS/2 keyboard/mouse
Ethernet	2 x 10/100/1000Mbps Ethernet	2 x 10/100/100Mbps Ethernet	2 x 10/100/100Mbps Ethernet
USB	6 x USB 2.0	6 x USB 2.0	6 x USB 2.0
Expansion Interface	1 x PCI	1 x PCIe x16	1 x PCIe x16
Storage	1 x 2.5" HDD	1 x 2.5" HDD	1 x 2.5" HDD
Watchdog Timer	255 levels, 0 - 255 sec.	255 levels, 0 - 255 sec.	255 levels, 0 - 255 sec.
Power Supply	120W ATX 90 - 264V _{AC}	250W ATX 90 - 264V _{AC}	250W ATX 90 - 264V _{AC}
Operating Temperature	0°C - +45°C (32°F - 113°F) (with W.T. HDD)	0°C - +45°C (32°F - 113°F) (with W.T. HDD)	0°C - +45°C (32°F - 113°F) (with W.T. HDD)
Wall Mount	Yes	Yes	Yes
DIN-rail	N/A	N/A	N/A
Dimensions (W x D x H)	300 x 210 x 104.5 mm (11.81" x 8.27" x 4.11")	300 x 210 x 104.5 mm (11.81" x 8.27" x 4.11")	300 x 210 x 104.5 mm (11.81" x 8.27" x 4.11")
Weight (net/gross)	6.3 kg (13.89 lb)/8.2 kg (18.08 lb)	6.3 kg (13.89 lb)/8 kg (17.64 lb)	6.3 kg (13.89 lb)/8 kg (17.64 lb)
Certification	CE	CE	CE
EOS Support	XPE, WinCE, Linux	XPE, WinCE, Linux	N/A

Embedded Systems - Vertical Market Solution

Selection Guide



Page 200



Page 201



Page 203

Features/Models	eHUB110	eBOX310-830-FL	eBOX646-FL
CPU Level	N/A	ULV Intel® Celeron® M 1.06 GHz/ Intel® Core™2 Duo/Core™ Duo/ Core™ Solo/Celeron® M up to 2.33 GHz	AMD LX800 500 MHz
System Memory	N/A	1 x 200-pin DDR2 SODIMM max. up to 2 GB	1 x 200-pin DDR SODIMM max. up to 1 GB
Chipset	N/A	Intel® 945GME+ICH7M	AMD LX800+CS5536
Serial	3 x Powered RS-232 (COM 1-3)	1 x RS-232/422/485 (COM 1) 2 x RS-232 (COM 2/3)	3 x RS-232 (COM 2/3/4) 1 x RS-232/422/485 (COM 1)
Display	N/A	1 x DVI-I	1 x VGA
Audio	N/A	1 x Audio (Line-in/Line-out)	N/A
LPT	N/A	N/A	0 (optional 1)
PS/2	N/A	1 x PS/2 keyboard/mouse	1 x PS/2 keyboard/mouse
Ethernet	N/A	2 x 10/100/1000Mbps Ethernet	2 x 10/100Mbps Ethernet
USB	4 x Powered USB 2.0	2 x USB 2.0	3 x USB 2.0
Expansion Interface	N/A	2 x PCI Express Mini Card	N/A
Storage	N/A	1 x 2.5" HDD 1 x CompactFlash™	1 x CompactFlash™
Watchdog Timer	N/A	255 levels, 1 - 255 sec.	255 levels, 0 - 255 sec.
Power Supply	120W 90 - 264V _{AC} adapter	80W intelligent vehicle power supply	20W 90 - 264V _{AC} adapter
Operating Temperature	0°C - +50°C (32°F - 122°F) (with W.T. HDD)	0°C - +50°C (32°C - 122°C) (with W.T. HDD)	-10°C - +50°C (14°F - 122°F) (with W.T. CF)
Wall Mount	N/A	Yes	Yes
DIN-rail	N/A	Yes	N/A
Dimensions (W x D x H)	200 x 139 x 40 mm (7.87" x 5.47" x 1.57")	205 x 250 x 56 mm (8.07" x 9.84" x 2.2")	200 x 150 x 44 mm (7.8" x 5.9" x 1.73")
Weight (net/gross)	1.5 kg (3.3 lb)/2 kg (4.4 lb)	3 kg (6.61 lb)/3.8 kg (8.37 lb)	1.3 kg (2.86 lb)/1.8 kg (3.97 lb)
Certification	CE	CE, ISO-7637	CE
EOS Support	N/A	XPE	XPE, WinCE, Linux

Embedded Systems - Vertical Market Solution

Selection Guide



Page 204

Features/Models	eBOX647-FL
CPU Level	VIA C7 1.5 GHz
System Memory	1 x 200-pin DDR2 SODIMM max. up to 1 GB
Chipset	VIA CX700M+ITE8888G
Serial	3 x RS-232 (COM 2/3/4) 1 x RS-232/422/485 (COM 1)
Display	1 x VGA
Audio	1 x Audio (Mic-in/Line-in/Line-out)
LPT	1 x LPT
PS/2	1 x PS/2 keyboard/mouse
Ethernet	1 x 10/100Mbps Ethernet
USB	3 x USB 2.0
Expansion Interface	N/A
Storage	1 x CompactFlash™
Watchdog Timer	255 levels, 0 ~ 255 sec.
Power Supply	60W 90 ~ 264V _{ac} adapter
Operating Temperature	0°C ~ +50°C (32°F ~ 122°F) (with W.T. CF)
Extended Temperature (Sorting)	N/A
Wall Mount	Yes
DIN-rail	Yes
Dimensions (W x D x H)	200 x 150 x 52.8 mm (7.87" x 5.90" x 2.07")
Weight (net/gross)	1.5 kg (3.31 lb)/2.6 kg (5.73 lb)
Certification	CE
EOS Support	XPE, WinCE, Linux