

15,0" LCD-TFT Monitor

DMXX 3234/3235/3236/3237



Key Features

Very High Brightness
Wide Viewing Angle
High Contrast Ratio
LVDS
Long Lamp Life
Short Response Time
Thin and Light



Inverter

LCD Display	15,0" TFT Active Matrix Panel
TouchScreen	optional
Brightness	1600 cd/m ²
Pixel Pitch	0.297 (H) x 0.297 (V) mm
Max. Resolution	1024 x 768
Contrast Ratio	500:1
Display Area	304.128 x 228.096 mm
Response Time	12ms (Typ.)
Display Colors	16.2M colors
Viewing Angle	+70° ~ -70° (H), +65° ~ -55° (V)
Video	RGB Analog 0.7V Peak to Peak
Sync	LVDS
Signal Connector	15 Pin D-sub, 29 Pin DVI-D
F/R Control Button	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
Power Consumption	56.5W
Dimensions	389 x 325 x 60.5mm (WxHxD)
Weight	3.92kg
Connectors	VGA/DVI, VGA/AV/S-Video or VGA only
Option	Light Sensor, VR Control

Ordering Information:

DMXX3234	15.0" TFT Monitor 1024 x 768 LVDS VGA/DVI High Brightness Einbaumonitor 1600 cd/m ² , ohne Touch
DMXX3235	15.0" TFT Monitor 1024 x 768 LVDS VGA/DVI High Brightness Einbaumonitor 1600 cd/m ² , mit Touch LiYi
DMXX3236	15" TFT LCD Monitor 1024 x 768 LVDS VGA/DVI High Brightness Einbaumonitor 1600 cd/m ² , mit Touch 3M resistiv
DMXX3237	15" TFT LCD Monitor 1024 x 768 LVDS VGA/DVI High Brightness Einbaumonitor 1600 cd/m ² , mit Touch 3M kapazitiv