



# 20,1" LCD-TFT Monitor

## DMXX 3260



### Key Features:

Covered with aluminum housing, build-in double ventilation fan system, LD2011 can deliver best quality pictures even in outdoor severe environment. Input signals include VGA, AV, S-Video, and optional TV Tuner for complete cable channel reception.

<b>LCD Display</b>	20,1" TFT Active Matrix Panel
<b>Brightness</b>	1.000 cd/m <sup>2</sup>
<b>Pixel Pitch</b>	0.51 x 0.51 (H x V)
<b>Resolution</b>	800 x 600
<b>Contrast Ratio</b>	500:1
<b>Display Area</b>	408 x 306 mm
<b>Response Time</b>	16 ms (Typ.)
<b>Display Colors</b>	16.7M
<b>Viewing Angle</b>	+85° ~-85° (H), +85° ~-80° (V)
<b>Horizontal/Vertical Frequency</b>	Hf: 31 ~ 80 KHz; Vf: 56 ~ 75 Hz
<b>Pixel Frequency</b>	135 MHz
<b>Signal Connector</b>	15 Pin D-sub, 29 Pin DVI
<b>Signal Connector (Video)</b>	S-Video / AV / Component
<b>Audio Output</b>	5W x 2 / 35x105x20 mm x 2
<b>AC/DC Power Adapter Input</b>	AC 100 ~ 240V, 50 ~ 60 Hz
<b>AC/DC Power Adapter Output</b>	DC 12V/6.66A
<b>Power Consumption</b>	80W (Max.)
<b>Temperature Range of Operation</b>	0 ~50 C
<b>Accessory</b>	Remote Control
<b>Weight</b>	N/W:8.08 kg
<b>Dimension</b>	507 x 415 x 63.1 (W x H xD) mm
<b>Option:</b>	
<b>Video Output</b>	BNC Video Out Jack
<b>TV-Tuner</b>	NTSC / PAL

### Ordering Information:

**DMXX3260** 20.1" TFT Monitor 800x600 TTL VGA only  
Einbaumonitor 1.000cd/m<sup>2</sup>, ohne TouchScreen