


# Special Solutions



The special solutions represent a variety of Panel PCs, mostly proprietary developments of DELTA COMPONENTS. Sophisticated design meets special requirements in versatile applications such as automotive computing, monitoring, ergometer, VoIP and much more.  
Ask DELTA COMPONENTS for further information.



Coming soon

Type	DeltaRack-PC	DeltaNav-PC IV	DeltaNav-PC IV	DeltaCardio-PC	MICROSPACE MPCF40-19
<b>Features</b>					
<b>Size</b>	6,5"	8,4"	10,4"	12,1" / optional 15" XGA	19"
<b>Resolution</b>	640 x 480	800 x 600	1.024 x 768	800 x 600	1.280 x 1024
<b>Brightness</b>	500 cd/m²	350 cd/m²	300 cd/m²	300 cd/m²	250 cd/m²
<b>Viewing Angle</b>	+50° ~ -60° (H); +35° ~ -45°				
<b>TouchScreen</b>	Resistive type Optional transflektiv	Resistive type	Resistive type	Resistive type	n/a
<b>CPU</b>	Pentium III VIA C3	Pentium III Intel Celeron VIA C3	Pentium III Intel Celeron VIA C3	VIA C3 Pentium III	Pentium M / Celeron M
<b>Clock Speed</b>	400MHz - 933MHz	400MHz - 933MHz	400MHz - 933MHz	400MHz - 933MHz	800MHz - 1,8GHz
<b>Chipset</b>	VT8606 (Twister-T) + VT82C686B	VT8606 (Twister-T) + VT82C686B	VT8606 (Twister-T) + VT82C686B	VT8606 (Twister-T) + VT82C686B	Intel 855GME
<b>Memory</b>	1x SDRAM SODIMM max. up to 512MB SDRAM	Up to 512 MB	Up to 512 MB	Up to 512 MB	512MB / 1GB
<b>Hard Disk Drive</b>	1x 2,5" HDD	1x IDE-Harddisk 2,5"	1x IDE-Harddisk 2,5"	1x IDE-Harddisk 2,5"	1x 40GB
<b>Optical Drive</b>	n/a	n/a	n/a	n/a	CD-R-Drive/CD-RW/DVDV-RW-Drive (optional)
<b>Floppy Disk Drive</b>	n/a	n/a	n/a	n/a	n/a
<b>I/O</b>	1x COM 1x RS-232 1x PS/2 1x USB 1.1 1x VGA/CRT 2x RJ-45 for LAN 100/10 BASE-T 1x Line-In 1x Line-Out 1x Mic-In	1x RJ-45 for Ethernet 10/100 BASE-T 1x PS/2 PCMCIA 2x typ II or 1x typ III 1x VGA/CRT 1x COM1 (GPS) 1x COM 2 (GSM) 4x USB ( 3x 2.0/ 1x 1.1) 1x Line-In 1x Line-Out 1x Mic-In	1x RJ-45 for Ethernet 10/100 BASE-T 1x PS/2 PCMCIA 2x typ II or 1x typ III 1x VGA/CRT 1x COM1 (GPS) 1x COM 2 (GSM) 4x USB ( 3x 2.0/ 1x 1.1) 1x Line-In 1x Line-Out 1x Mic-In	1x RJ-45 for Ethernet 10/100 BASE-T 1x PS/2 1x RS-232 3x RS-232/422/485 internal 1x USB 1x VGA/ CRT 2x PCMCIA 1x Line-In 1x Line-Out 1x Mic-In	1x RJ-45 for Ethernet 10/100 BASE-T 2x PS/2 2x USB 2.0 1x DVI 1x VGA/CRT 1x Line-In 1x Line-Out 1x Mic-In
<b>Video Controller</b>	VIM Twister S3 PRO	VIM Twister S3 PRO	VIM Twister S3 PRO	VIM Twister S3 PRO	Intel 855GME in North Bridge
<b>Expansion</b>	CompactFlash Type II	CompactFlash Type II, PCMCIA	CompactFlash Type II, PCMCIA	1x CompactFlash	1x Mini-PCI
<b>Watchdog Timer</b>	yes	yes	yes	yes	yes
<b>Operating Temperature</b>	0° ~ 50°C	0° ~ 60°C	0° ~ 60°C	0° ~ 50°C	5°C ~ 50°C
<b>Cooling system</b>	with fan	with fan	with fan	with fan	fanless
<b>Operating System</b>	Win 2000 / XP QNX, others on request	Win 2000 / XP QNX, others on request	Win 2000 / XP QNX, others on request	Win 98 / ME / NT / 2000 / XP	Win 2000 / XP Linux and more
<b>Dimension (mm)</b>	215 x 130 x 130	258,0 x 214,0 x 61,0	258,0 x 214,0 x 61,0	400,0 x 320,0 x 80,0	302,0 x 249,0 x 104,0
<b>Weight</b>	1,9 kg	1,8 kg	1,8 kg	5,2 kg	3,0 kg
<b>Power Input</b>	12 VDC	8 - 28 VDC	8 - 28 VDC	8 - 28 VDC	10 - 30 VDC
<b>Front Bezel</b>					aluminium black
<b>Protection class</b>					IP50
<b>Features</b>	Brightness Control via potentiometer	GPS/ GSM-GPRS Sound: 2 speakers internal 2,5" HDD (Standard-, Server-, Automotive-Grade)	GPS/ GSM-GPRS Sound: 2 speakers internal 2,5" HDD (Standard-, Server-, Automotive-Grade)		without Monitor available
<b>Ordering Number</b>	PKRX1021-V11	PKKC3010	PKKC3000	t.b.d.	PKBX1018

Special Solutions